

## CONVENTIONAL POLYCARBONATE HOUSE POLY

Stock Range and Size Outline

SPHERE	-CYLINDER																
MINUS	0	0	0 5	7	1	1	1	7	2	2	2	2 7	3	3	3	3 7	4
-	0	5	0	5	0	5	0	5	0		0	5	0		0	5	(
-000																	
-025																	
-050																	
-075																	
-100																	
-125																	
-150																	
-175																	
-200																	
-225																	
-250																	
-275																	
-300																	
-325																	
-350																	
-375																	
-400							7	6r		_							
-425							-/	OI	ш	П							
-450																	
-475																	
-500																	
-525																	
-550																	
-575																	
-600																	
-625																	
-650																	
-675																	
-700																	
-725																	
-750																	
-775																	
-800																	
-825																	
-850																	
-875																	
-900																	
-925																	
-925 -950																	
-975																	
313																	

SPHERE	-CYLINDER									
PLUS +			5	0 7 5					2 0 0	
+000 +025										
+050 +075										
+100										
+125 +150										
+175				63	m	ım				
+200 +225										
+250 +275										
+300										

Specification						
Materials	Polycarbonate					
Refractive Index	1.59					
Density (g. cm <sup>-3</sup> )	1.20					
Abbe Vaule	30					
UV cut off	380nm					
Design	Double Aspherical					